

DESCOTE® ZINC OXIDE 50% ULTRA

Product Code: 9-4845

PRODUCT DESCRIPTION

Descote® Zinc Oxide 50% Ultra is a white to off-white, relatively free flowing material. Each gram of coated material is manufactured to contain 500mg of Zinc Oxide, USP in a matrix of Mono- and Diglycerides, FCC. Where the component of the product blend is of vegetable origin, Particle Dynamics has obtained from the supplier a certification that the component of interest is not produced from genetically modified organisms.

PARAMETERS	SPECIFICATIONS
Assay – Zinc Oxide	485-550 mg/g
Identification	Positive
Particle Size:	
#20 U.S. Std. Sieve	NMT 2% On
#60 U.S. Std. Sieve	NMT 50% On
#200 U.S. Std. Sieve	NMT 30% Through
Lead	NMT 6 ppm
Description	White to off-white, relatively free flowing material which may contain agglomerates

STABILITY

Descote® Zinc Oxide 50% Ultra (Low Lead) is physically and chemically stable when stored in a dry, cool location, preferably a controlled room temperature between 59° - 86° F (15° - 30°C).

Packaged in 50 kg fiber board drums with steel locking rims with two polyethylene liners

This Product Data Sheet has been compiled from information believed to be accurate and reliable. However, Particle Dynamics MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, EITHER WITH TO THE INFORMATION PROVIDED OR THE PRODUCT DESCRIBED, (INCLUDING ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), and same should not be deemed or relied upon as a substitute for testing of the product herein described by purchaser or of any product into which it is incorporated.

This Product Data Sheet does not represent an offer or agreement by Particle Dynamics to sell the product herein described. Any such offer or agreement will be subject to Particle Dynamics' standard terms and conditions which will be made available upon request.